



RT 8305-21G

| | |
|-----------------------|---|
| Processeur | <ul style="list-style-type: none"> • Intel Pentium 4 à 2 GHZ avec cache L2 • bus system 533 MHZ |
| Cache | <ul style="list-style-type: none"> • 512KB |
| Chipsets | <ul style="list-style-type: none"> • Intel 845G chipset • Memory Controller Hub (MCH) • I/O Controller Hub (ICH4) for PCI 2.2 bus • Integrated 10/100 Mbit LAN controller • SMBUS device support |
| Mémoire | <ul style="list-style-type: none"> • 256 Mo 266MHz DDR (Double Data Rate) RAM • 2 DIMM sockets (1 open) • 2 - 184-pin DIMMS • Supports a maximum memory up to 2.0GB |
| Disque dur | <ul style="list-style-type: none"> • 40 Go, ATA-100 7200RPM |
| CD-ROM | <ul style="list-style-type: none"> • Enhanced IDE/ATAPI interface • Less than 85 ms average access time and 128 KB buffer for look-ahead cache • 12 cm and 8 cm disc compatibility (8 cm horizontal mount only) |
| Audio | <ul style="list-style-type: none"> • Integrated digital audio • SoundMAX 3.0 with SPX. • Software-based audio (done by processor and ICH4) • AC '97 interface |
| Alimentation | <ul style="list-style-type: none"> • 185 watt supply with variable speed fan • 110 volt or 220 volt operation controlled by a switch on the back of the unit |
| Ports externes | <ul style="list-style-type: none"> • Six USB (two in front, four in back) [Ver 2.0] • One ethernet RJ-45 • Two serial 9-pin • One parallel (EPP, ECP), IEEE 1284 |
| Ports internes | <ul style="list-style-type: none"> • Slot 1: 32-bit AGP 4X (1.5v) Slot 2,3,4: 32-bit PCI 2.2 (5v) |

Produit re-construit à partir de composants neuf et d'occasion